

CE Ex II 2 G/D c IIC T6 (85°C)

Characteristics



Static
Dissipating



HEPA Included



High
Efficiency



Stainless
Steel



Static
Dissipating
Toolkit



Wet & Dry
Applications



Stainless steel SAE 430 body and recovery tank. Contains a true HEPA Filter (H14) located upstream. This unit is static dissipating and conductive (Category 3 - Zone 22 (Dust)) and can be used for general maintenance. This unit cannot be used to recover conductive or combustible dusts or flammable liquids. With a powerful suction this unit is designed for industrial applications. All of our HEPA vacuum cleaners are Aerosol Leak Tested before leaving our facility.

Specifications

	Unit	ATEX-12A
Part#		111962
Weight	lbs	25
Filter Cleaning		NONE
Decibels	dB	68
Dimensions	Inches	H32 × W19 × L21
Wet Recovery	Gal	12.6
Dry Recovery	Gal	10
Vacuum Pressure	Inches H ₂ O	110
Air Flow	CFM	110
Venturi		Single
Minimum Compressor HP	HP	15
Air Line Size		1/2"
Input Air Volume	CFM	35
Input Air Pressure	PSI	80

High Efficiency Particulate Air Filter

A HEPA filter is a type of air filter, which means it filters the air coming in or out of the vacuum cleaner system. It can remove at least 99.99% of dust, pollen, mould, bacteria and any other airborne particles with a size of 0.3 micron or larger.

North-America: Each HEPA Filter has a minimum filtration efficiency of 99.99% on 0.3 micron. Tested as per IEST-RP-CC001.3 and OSHA compliant.

Europe: Each HEPA Filter has a minimum filtration efficiency of 99.995% on 0.3 micron, rated H14 as per EN 1822 by MPPS method.

HEPA FILTER - Included

Part#	Qty	Description
212304B	1	HEPA FILTER (H14)

FILTERS - Included

Part#	Qty	Description
211430T	1	MAIN FILTER ASSEMBLY, PTFE LAMINATED, w/YELLOW GASKET, w/RING #214279 FOR USE WITH POLY TANKS
211394	1	LIQUID FILTER ASSEMBLY

TOOLS AND ACCESSORIES - Included

Part#	Qty	Description
383440B	1	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASSEMBLY(NO WIRE)Ø1.5"(38mm)x10'(3m) FOR 2" CAMLOCK INTAKE
211029C	1	AIR SUPPLY HOSE ASMBLY SD* Ø0.5"(12.7mm)x25'(7.5m) WITH MALE NPT ON ONE END & CHICAGO ON OTHER END
381208	1	CURVED HANDLE Ø1.5"(38mm) TO Ø1.25"(32mm) -CHROME
323315	1	EXTENSION WANDS Ø1.25"(32mm)(SET OF 2) -CHROME
323318A	1	UTILITY FLOOR TOOL, Ø1.25"(Ø32mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES
323317A	1	UTILITY FLOOR TOOL, 1.25"(Ø32mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/GREY SQUEEGEE BLADES
323312A	1	ROUND BRUSH, Ø1.25"(32mm), ESD SAFE PLASTIC
323313A	1	CREVICE TOOL, Ø1.25"(32mm), ESD SAFE PLASTIC

TOOLS AND ACCESSORIES - Included		
Part#	Qty	Description
323314A	1	UPHOLSTERY FLAT TOOL, Ø1.25"(32mm), ESD SAFE PLASTIC

Ø1.5" (Ø38mm) SUCTION HOSE / EXTENSION HOSE PARTS AND ACCESSORIES - Optional		
Part#	Qty	Description
383438-50	1	CRUSHPROOF SUCTION HOSE, STATIC CONDUCTIVE (NO WIRE) 50'(15m)xØ1.5"(38mm)
383434	1	HOSE CUFF UNION WITH SWIVEL Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383436	1	HOSE CUFF Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383435	1	EXPANDER HOSE CUFF Ø1.5"(38mm) TO Ø2"(Ø50mm) STATIC CONDUCTIVE -BLACK
500175	1	CAMLOCK SPECIAL PART C Ø2"(50mm)FEMALE ADAPTOR TO Ø1.5"(38mm)HOSE SHANK -ALUMINUM

TOOLS AND ACCESSORIES - Optional		
Part#	Qty	Description
381477	1	DOUBLE BEND WAND 2 PC) -CHROME
381448A	1	UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES
381447A	1	UTILITY FLOOR TOOL, 1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/GREY SQUEEGEE BLADES
381155A	1	REDUCER, TAPERED 1.5"(38mm) TO 1.25"(Ø32mm) ALUMINUM

WARNINGS:

This unit can only be used in presence of combustible dust and flammable liquids but cannot be used to recover combustible dusts and flammable liquids.



Arc Technologies

Worldwide Technology For Controlled Environments

Web site: www.arctechnologies.co.uk

email: achambers@arctechnologies.co.uk

Tel: +(44)0115 928 1508