



**GUARANTEED** to be capable of safely recovering combustible/conductive dusts &/or flammable liquids.

CE II 2 G/D c IIC T6 (85°C)

**LCIE 03 ATEX 6310** Vacuum Cleaner certified for providing an Equipment Protection Level of EPL Db and EPL Gb

### Characteristics



Explosion Proof



Resistivity: Less than 10 ohms



HEPA Included



ULPA Optional



Activated Carbon



Wet & Dry Applications



High Efficiency



Stainless Steel AISI 304



Static Dissipating Toolkit



- Legally certified explosion proof/dust ignition proof by a recognized testing laboratory
- Less than 10 Ohms of resistivity
- HEPA Filter - Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001.3. H14 by MPPS method as per EN 1822. Or ULPA Filter - Optional with an efficiency of 99.999% on 0.12 micron. Tested: IEST RP-CC001.3. Filtration efficiency of 99.9995% on 0.18 micron. Tested: IEST RP-CC001.3. U15 by MPPS method as per EN 1822.
- For general cleanup in hazardous locations
- Pneumatically (air) operated
- Equipped with a Middle Ring with Activated Carbon Cartridge for the adsorption of fumes and vapors
- For wet & dry recovery
- All stainless steel SAE 304 construction
- Recovery tank capacity of 7.5 gallons (28.5 liters) - wet and 6 gallons (23 liters) - dry
- Optional SD\* polyliner and clip available for easy and safe disposal of recovered materials
- Based on an SD\* 4-wheel dolly for easy manoeuvrability
- Complete static dissipating tool kit and suction hose included

SD\* Static Dissipative

All stainless steel SAE 304 construction. Less than 10 Ohms of resistivity. This unit is equipped with a true HEPA Filter (H14) located downstream. This unit is also equipped with a Middle Ring and Activated Carbon Cartridge for the adsorption of toxic/nuisance fumes and vapors. This unit can be used for general maintenance in hazardous locations. This is a wet & dry vacuum cleaner. Recovery capacity is 7.5 gallons (28.5 liters) - wet and 6 gallons (23 liters) - dry. All of our HEPA vacuum cleaners are Aerosol Leak Tested before leaving our facility.

## Specifications

	Unit	SS-10 (4W) RE HEPA (MRAC)
Part#		110366
Filter Cleaning		NONE
Decibels	dB	70
Wet Recovery	Gal	7.5
Dry Recovery	Gal	6
Vacuum Pressure	Inches H <sub>2</sub> O	180
Air Flow	CFM	110
Venturi		Single
Minimum Compressor HP	HP	15
Air Line Size		1/2"
Input Air Volume	CFM	45
Input Air Pressure	PSI	80
Airjet		6mm

## High Efficiency Particulate Air Filter

A HEPA filter is a type of air filter, which means it filters the air coming in or out of the vacuum cleaner system. It can remove at least 99.99% of dust, pollen, mould, bacteria and any other airborne particles with a size of 0.3 micron or larger.

North-America: Each HEPA Filter has a minimum filtration efficiency of 99.99% on 0.3 micron. Tested as per IEST-RP-CC001.3 and OSHA compliant.

Europe: Each HEPA Filter has a minimum filtration efficiency of 99.995% on 0.3 micron, rated H14 as per EN 1822 by MPPS method.

## Explosion Proof Requirement

In order for Tiger-Vac to legally certify an Explosion Proof/Dust Ignition Proof vacuum cleaner system the unit must be static dissipative (SD\*) and conductive and have a resistivity measuring less than 10 Ohms to any point on the vacuum cleaner system. This makes the unit eligible to be Explosion Proof/Dust Ignition Proof and be part of Tiger-Vac's quality control management system ISO 9001:2008.

When using a pneumatic Explosion Proof Vacuum Cleaner System the customer must make sure that the source of air supply (compressor) is grounded.

## Ex-Mat Recovery



Tiger-Vac, as the manufacturer, GUARANTEES, that these units can be used to safely recover combustible /conductive dusts and/or flammable liquids.

The ATEX marking certifies only, by it's Ingress of Protection (IP), the capacity of the vacuum cleaner to be in the presence of combustible /conductive dusts and/or flammable liquids but does not certify the capacity of the vacuum cleaner to recover them.



**Arc Technologies**

Worldwide Technology For Controlled Environments

Web site: [www.arctechnologies.co.uk](http://www.arctechnologies.co.uk)

email: [achambers@arctechnologies.co.uk](mailto:achambers@arctechnologies.co.uk)

Tel: +(44)0115 928 1508

## Ultra Low Penetration Air Filter

A ULPA filter is a type of air filter. It can remove at least 99.999% of dust, pollen, mould, bacteria and any other airborne particles with a size of 0.12 microns or larger.

North-America: Each ULPA Filter has a minimum filtration efficiency of 99.999% on 0.12 micron. Tested as per IEST-RP-CC001.3.

Europe: Each ULPA Filter has a minimum filtration efficiency of 99.9995% on 0.18 micron, rated U15 as per EN 1822 by MPPS method.

HEPA FILTER - Included		
Part#	Qty	Description
211027B	1	HEPA FILTER (H14)

FILTERS - Included		
Part#	Qty	Description
211013	1	MAIN FILTER ASSEMBLY SD* FOR 10/15/25 GALLON EXPLOSION PROOF VACS
212008	1	PRE-FILTER ASSEMBLY SD* (10,15&25 GALLON)
211010	1	LIQUID FILTER ASSEMBLY SD* FOR 10/15/25 GAL EXP PROOF VACS

ACTIVATED CARBON CARTRIDGES - Optional		
Part#	Qty	Description
212200B	1	CARBON CARTRIDGE ASSEMBLY WITH 3mm CARBON (REGULAR)
212200C	1	CARBON CARTRIDGE ASSEMBLY WITH 3mm MERSORB (FOR MERCURY VAPORS)
212200K	1	CARBON CARTRIDGE ASSEMBLY WITH 3mm KOGC3/KINA3 CARBON (FOR CHLORIDE VAPORS)
212200L	1	CARBON CARTRIDGE ASSEMBLY WITH 3mm A-3 CARBON (FOR ARSINE AND PHOSPHINE VAPORS)

POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional		
Part#	Qty	Description
212100A	1	CONDUCTIVE POLY LINER WITH HOLE FOR SUCTION INLET
213780	1	POLY LINER RETAINER PLATE WITH CLIP

TOOLS AND ACCESSORIES - Included		
Part#	Qty	Description
381050	1	NITRILE SUCTION HOSE ASSEMBLY, SD*, Ø1.5"(38mm)x10'(3m) FOR Ø1.5"(38mm) CAMLOCK INTAKE -ALUMINUM
211030	1	AIR SUPPLY HOSE ASSEMBLY SD* Ø0.5"(12.7mm)x50'(15m) WITH 1 MALE QUICK DISC. & 1 FEMALE QUICK DISC.
211033B	1	FEMALE QUICK DISCONNECT Ø0.5"(12.7mm) WITH Ø0.5"(12.7mm) FEMALE THREAD (BRASS)
211095C	1	HEX NIPPLE -BRASS (0.5"NPT)
381364	1	WAND ASSEMBLY (2PC) STAINLESS STEEL WITH ALUMINUM ATTACHMENT
381236	1	UNIVERSAL TOOL SD* W/CONDUCTIVE BRUSH STRIPS,RUBBER BLADES,BRASS AXLE&WHEELS Ø1.5"(38mm)x18"(45.7cm)
381188	1	CREVICE TOOL SD* 11"(27.9cm), ALUMINUM
381190	1	CONICAL NOZZLE ASSEMBLY 6"(15.2cm) -NITRILE
381219	1	CONICAL NOZZLE ASSEMBLY 21"(53.3mm) -NITRILE
211065B	1	MULTIMETER

GROUNDING REEL - Optional		
Part#	Qty	Description
211191	1	GROUNDING REEL WITH STAINLESS STEEL CABLE WITH AIRCRAFT GROUNDING CLAMP 50'(15m)



**Arc Technologies**

Worldwide Technology For Controlled Environments

Web site: [www.arctechnologies.co.uk](http://www.arctechnologies.co.uk)

email: [achambers@arctechnologies.co.uk](mailto:achambers@arctechnologies.co.uk)

Tel: +(44)0115 928 1508

## WARNINGS:

For the recovery of metallic dusts, it is recommended that this unit be used in conjunction with an immersion separator

Only tools and accessories provided by Tiger-Vac shall be used with this vacuum cleaner. Any other tools used will render the warranty null and void and may cause an explosion which could result in bodily harm. Tiger-Vac will not assume any responsibility for damage that may occur due to the improper use or handling of the vacuum cleaner system.



**Arc Technologies**

Worldwide Technology For Controlled Environments

Web site: [www.arctechnologies.co.uk](http://www.arctechnologies.co.uk)

email: [achambers@arctechnologies.co.uk](mailto:achambers@arctechnologies.co.uk)

Tel: **+(44)0115 928 1508**